

Element Name	Attribute name	Required	Default value	Mnemonic	Comments
					Can contain many child <target> Elements
NotificationList	type	y		NotificationList.TYPE	"ok" or "error"
target	class	y		NotificationTarget.PRM_NOTIF_CLASS	
If target.class = NotifyEmail					
	sendTo	y		Email.SENDTO	
	from	y		Email.FROM	
	ccTo	n	null	Email.COPYTO	
	subject	n	null	Email.SUBJECT	
	message	n	null	Email.MESSAGE	
	NotifyEmail can have (0,n) <attachment> element children				
	e.g. <attachment>/var/log/abcde</attachment> <attachment>/tmp/myfile1</attachment>				
If target.class = NotifyFiles					
	NotifyFiles has no attributes but can have (1,n) <file> element children				
file	URI	y		NotifyFiles.CHILD_FILE NotifyFiles.ATT_URI	
	append	n	false	NotifyFiles.ATT_APPEND	
If target.class = NotifyQueues					
	No attributes Can have (1,n) <queue> element children				
<queue>	jndiName	y		NotifyQueues.CHILD_QUEUE NotifyJMS.ATT_DEST_NAME	
	Can have (0,n) <messageProp> element children				
messageProp	name	y		NotifyJMS.CHILD_MSG_PROP NotifyJMS.ATT_PROP_NAME	
	value	y		NotifyJMS.ATT_PROP_VALUE	
If target.class = NotifyTopics					
	No attributes Can have (1,n) <topic> element children				
<topic>	jndiName	y		NotifyTopics.CHILD_TOPIC NotifyJMS.ATT_DEST_NAME	
	Can have (0,n) <messageProp> element children (see messageProp in NotifyQueues)				