

Element Name	Attribute name	Required	Default value	Mnemonic	Comments
GpListener root node (1)					
any	commandConnFactoryClass	n	ConnectionFactory	GpListener.COMMAND_CONN_FACTORY	
There must always be a root node even if none of it's attributes are set					
any	commandJndiType	n	jboss	GpListener.COMMAND_JNDI_TYPE	
any	commandJndiURL	n	localhost	GpListener.COMMAND_JNDI_URL	
any	commandsTopic	n	false	GpListener.COMMAND_IS_TOPIC	
any	commandJndiName	n	null	GpListener.COMMAND_JNDI_NAME	
any	messageSelector	n	null	GpListener.COMMAND_MSG_SELECTOR	
any	parameterReloadSecs	n	180 secs	GpListener.PARM_RELOAD_SECS	
any	endTime	n	forever	GpListener.PARM_END_TIME	yyyyMMdd hh:mm:ss
Email configuration child element (0,1)					
EmailProperties	org.jboss.soa.esb.mail.smtp.host	n	localhost	SystemProperties.SMTP_HOST	
EmailProperties	org.jboss.soa.esb.mail.smtp.user	n	null	SystemProperties.SMTP_USERNAME	
EmailProperties	org.jboss.soa.esb.mail.smtp.password	n	null	SystemProperties.SMTP_PASSWORD	
EmailProperties	org.jboss.soa.esb.mail.smtp.port	n	25	SystemProperties.SMTP_PORT	
EmailProperties	org.jboss.soa.esb.mail.smtp.from	n	null	SystemProperties.SMTP_FROM	
EmailProperties	org.jboss.soa.esb.mail.smtp.auth	n	false	SystemProperties.SMTP_AUTH	
If present, must be an immediate child of the root node					
Child listener classes (1,*)					
any (except EmailProperties) Can be any of the listener types described below (DirectoryPoller, SqTablePoller, JmsQueueListener)					
DirectoryPoller configuration					
DirectoryPoller	listenerClass	y		GpListener.PARM_LISTENER_CLASS	
DirectoryPoller	actionClass	y		GpListener.PARM_ACTION_CLASS	
DirectoryPoller	maxThreads	n	1	GpListener.PARM_MAX_THREADS	
DirectoryPoller	pollLatencySecs	n	20	AbstractPoller.PARM_POLL_LTCY	
DirectoryPoller	inputDirURI	y		DirectoryPoller.FILE_INPUT_DIR	
DirectoryPoller	inputSuffix	y		DirectoryPoller.FILE_INPUT_SFX	
DirectoryPoller	workDir	n	.esbWork	DirectoryPoller.FILE_WORK_SF	
DirectoryPoller	errorDirURI	n	defaults to inputDir	DirectoryPoller.FILE_ERROR_DIR	
DirectoryPoller	errorSuffix	n	.esbError	DirectoryPoller.FILE_ERROR_SF	
DirectoryPoller	postDirURI	n	defaults to inputDir	DirectoryPoller.FILE_POST_DIR	
DirectoryPoller	postSuffix	n	.esbDone	DirectoryPoller.FILE_POST_SF	
DirectoryPoller	postDelete	n	false	DirectoryPoller.FILE_POST_DEL	If true, postDirURI and postSuffix are ignored
Must be org.jboss.soa.esb.listeners.DirectoryPoller					
Must specify a class that extends AbstractFileAction					
SqTablePoller configuration					
SqTablePoller	listenerClass	y		GpListener.PARM_LISTENER_CLASS	
SqTablePoller	actionClass	y		GpListener.PARM_ACTION_CLASS	
SqTablePoller	maxThreads	n	1	GpListener.PARM_MAX_THREADS	
SqTablePoller	pollLatencySecs	n	20	AbstractPoller.PARM_POLL_LTCY	
SqTablePoller	driver-class	y		SimpleDataSource.DRIVER	
SqTablePoller	connection-url	y		SimpleDataSource.URL	
SqTablePoller	user-name	n	zero length string	SimpleDataSource.USER	
SqTablePoller	password	n	zero length string	SimpleDataSource.PASSWORD	
SqTablePoller	tableName	y		SqTablePoller.TABLE_ATT tableName	
SqTablePoller	selectFields	y		SqTablePoller.TABLE_ATT selectFields	All fields in this list must also be in the selectFields list
SqTablePoller	keyFields	y		SqTablePoller.TABLE_ATT keyFields	
SqTablePoller	inProcessField	y		SqTablePoller.TABLE_ATT inProcessField	Used to avoid concurrent access to same row
SqTablePoller	whereCondition	n	null	SqTablePoller.OPTIONAL_ATT whereCondition	
SqTablePoller	orderBy	n	null	SqTablePoller.OPTIONAL_ATT orderBy	
Must be org.jboss.soa.esb.listeners.SqTablePoller					
Must specify a class that extends AbstractSqlRowAction					
JmsQueueListener configuration					
JmsQueueListener	listenerClass	y		GpListener.PARM_LISTENER_CLASS	
JmsQueueListener	actionClass	y		GpListener.PARM_ACTION_CLASS	
JmsQueueListener	maxThreads	n	1	GpListener.PARM_MAX_THREADS	
JmsQueueListener	queueConnFactoryClass	n	ConnectionFactory	JmsQueueListener.LISTEN_QUEUE_CONN_FACT	
JmsQueueListener	listenJndiType	n	jboss	JmsQueueListener.LISTEN_JNDI_TYPE	
JmsQueueListener	listenJndiURL	n	localhost	JmsQueueListener.LISTEN_JNDI_URL	
JmsQueueListener	listenQueue	y		JmsQueueListener.LISTEN_QUEUE	
JmsQueueListener	listenMsgSelector	n	null	JmsQueueListener.LISTEN_MSG_SELECTOR	
If DirectoryPoller is configured with actionClass="org.soa.esb.actions.FileCopier" it must contain (1,n) child elements <CopyTo>					
<CopyTo> element					
<CopyTo> element	copyToDirURI	y			
<CopyTo> element	copyToSuffix	y			