JMX Tools Reference Guide

Version: 3.3.0.M5

1. Introduction 1
1.1. What is JMX Tools? 1
1.2. Key Features of JMX Tools 3
2. JMX Tools Tasks
2.1. Quick Start 5
2.2. Managing Application 5
2.3. Tomcat Managing 9
2.4. Managing a JBoss application server remotely
2.5. Extension Task 10
2.5.1. Why you extend the framework 10
2.5.2. Core Extensions 10
2.5.3. UI Extensions 10
2.6. Connections Creation Task 11
2.6.1. Establishing Connection 11
3. References
3.1. MBean Explorer 13
3.2. MBean Editor 15
3.2.1. Notifications Page 17
4. Summary
4.1. Other relevant resources on the topic 19

Introduction

JBoss Tools' JMX project is a fork of *eclipse-jmx* [http://code.google.com/p/eclipse-jmx/], a project by Jeff Mesnil. It was forked with permission.

1.1. What is JMX Tools?

JBoss JMX ToolsTM allows you to setup multiple JMX connections, and provides a view for exploring the JMX tree and execute operations directly from within Eclipse.

This chapter covers the basics of working with JMX plugin[™], which is used to manage Java applications (with Managed Beans) through JMX and its RMI Connector.

java.lang.Strir boolean void void void void void void void	listDeployedURLs hasURL start removeURL addURL removeURL stop	java.lang.String java.lang.String java.net.URL java.net.URL
void void void void void	start removeURL addURL removeURL stop	java.lang.String java.net.URL
void void void void	removeURL addURL removeURL stop	java.net.URL
void void void	addURL removeURL stop	java.net.URL
void void	removeURL stop	•
void	stop	java.net.URL
void		
	addURL	java.lang.String
boolean	hasURL	java.net.URL

Figure 1.1. JMX Tools

1.2. Key Features of JMX Tools

The table below lists the main features of JBoss JMX Tools:

Table 1.1. Key Functionality for JBoss JMX Tools

Feature	Benefit	Chapter
MBean Explorer	MBean Explorer is a useful view with a text filter that displays domains, mbeans, attributes, and operations inside a connection.	mbean_explorer
MBean Editor	MBean Editor is a multi-page editor to manage MBeans.	mbean_editor

JMX Tools Tasks

This chapter will provide answers to common questions asked by JMX plugin users.

2.1. Quick Start

To start using the JMX Tools it is necessary to open **MBean Explorer**. Select **Window** \rightarrow **Show View** \rightarrow **Other**, select **MBean Explorer** and click the **OK** button.

The **MBean Explorer** lists all the domains, MBeans, attributes, and operations inside a connection. When you double-click an MBean in the **MBean Explorer**, it opens a multi-page editor to manage the MBean. The **MBean Editor** is composed of these pages:

- Attributes page, to get/set the attributes of the MBean
- · Operations page, to invoke operations on the MBean
- Notifications page, to receive notifications from the MBean
- Info page, which displays general information about the MBean

2.2. Managing Application

In this section we will show you how to get connected to a sample Java application and run the sayHello() method remotely from inside of the **MBean Explorer**.

- 1. Save the bundle of JMX API sample classes, *jmx_examples.zip* [http://java.sun.com/docs/ books/tutorial/jmx/examples/jmx_examples.zip], to your working directory.
- 2. Unzip the bundle of sample classes.
- 3. Compile the example Java classes from within where you unpacked the files directory.

```
javac com/example/*.java
```

4. Start the Main application, specifying the properties that expose Main for remote management:

```
java -Dcom.sun.management.jmxremote.port=9999 \
-Dcom.sun.management.jmxremote.authenticate=false \
-Dcom.sun.management.jmxremote.ssl=false \
com.example.Main
```

If everything was done correctly you will see the

Waiting for incoming requests...

message on the screen.

- ^{5.} Now launch the Eclipse IDE, in Eclipse open the **MBean Explorer**. Go to **Window** \rightarrow **Show View** \rightarrow **Other**, select **MBean Explorer**, and then click the **OK** button)
- 6. Click the **New Connection** icon



in the MBean Explorer menu bar.

- 7. In the Create JMX Connection dialog, click the Next button and then click the Advanced tab.
- 8. In the JMX URL input field enter the following URL:

service:jmx:rmi:///jndi/rmi://:9999/jmxrmi

۹	Create JMX Connection	×
Create a r	new JMX Connection	
Create a n the Advance	ew Default JMX Connection type by filling out either the Simple or ced tab.	
Simple A	dvanced	
Name	JMX Server	
JMX URL	service:jmx:rmi:///jndi/rmi://:9999/jmxrmi	
Username		
Password		
?	< Back Next > Cancel Finit	sh

Figure 2.1. JMX Connection

- 9. Click the **Finish** button to establish the connection with the application.
- 10Now expand the connection you have just created, open the **com.example** package, and click the sayHello() method.

Once the sayHello() method is selected the **MBean Editor** is activated.

11Jn the **MBean Editor** go to the **Operation Details** section and click the sayHello() button.

You will get the "Operation invoked successfully" message.



12.The final step is to make sure the application worked as expected. Open the terminal where you launched the application in step 3. You should see output similar to the following:

```
[matthew@localhost jmx_examples]$ java -
Dcom.sun.management.jmxremote.port=9999 \
> -Dcom.sun.management.jmxremote.authenticate=false \
> -Dcom.sun.management.jmxremote.ssl=false \
> com.example.Main
Waiting for incoming requests...
hello, world
```

2.3. Tomcat Managing

It is possible to manage Tomcat using JMX Tools.

Currently, JMX Tooling is able to connect to Tomcat without authentication or with passwordbased authentication.

Using SSL for authentication is not supported: you need to make sure that the System property **com.sun.management.jmxremote.ssl** is set to false.

More information to manage Tomcat can be found in the *Tomcat management documentation* [http://tomcat.apache.org/tomcat-7.0-doc/].

Instructions to remotely manage Tomcat are available in *Tomcat's monitoring documentation* [http://tomcat.apache.org/tomcat-7.0-doc/monitoring.html].

2.4. Managing a JBoss application server remotely



Important

If you are running JBoss Enterprise Application Platform 6, JBoss Application Server 7 or later, you can connect automatically to a remote server through the **Server Behaviour** tab in the server settings. For further information on this see the *JBoss Server Manager Reference Guide* for this release.

The JBoss JMX Tools allow you to easily access and manage a JBoss server remotely. In order to connect to a remote instance of a JBoss server, you need to run the server or make sure the server is launched.

- ^{1.} Select Window \rightarrow Open Perspective \rightarrow Other and select the JMX perspective option.
- 2. Switch to the MBean Explorer by selecting Window \rightarrow Show View \rightarrow Other and selecting the MBean Explorer option.

3. Click	the	New	Connection	icon
-				

the MBean Explorer menu bar.

4. Select the Advanced tab and set the JMX URL to:

service:jmx:rmi://localhost/jndi/rmi://localhost:1090/jmxconnector

Please note that in this example we are connected to the local host.

2.5. Extension Task

This section will outline how to contribute your own Server type with some default behavior.

2.5.1. Why you extend the framework

You might be asking yourself why you would need to extend this framework if JMX is a standard. Perhaps you want a connection to be automatically created after some specific action, or perhaps you want your connection wizard to do more than simply set a host and port. JBoss, for example, requires setting some credentials on the client machine, but uses JBoss classes to do it. This requires that the connection has access to the JBoss JARs.

2.5.2. Core Extensions

JMX То Connection the create your own must use type, you org.jboss.tools.jmx.core.MBeanServerConnectionProvider extension point. This point takes one child, a connectionProvider with a implements class that org.jboss.tools.jmx.core.IConnectionProvider.

An IConnectionProvider is responsible for creation and deletion of IConnectionWrapper objects. It must also keep a list of listeners that it is expected to notify when a connection is added or removed from its list.

Each IConnectionWrapper is expected to be able to run arbitrary JMX runnables or getting a "Root" object representing all JMX nodes. There are some utility methods the IConnectionWrapper can make use of.

2.5.3. UI Extensions

There are two extension points currently approved for use in the UI

• org.jboss.tools.jmx.ui.providerUI - provide an icon, id, displayable name, and wizardPage class for creation of new connections

• org.jboss.tools.jmx.ui.attribute.controls - allows you to map class types to some Control to present them in the MBean Editor

2.6. Connections Creation Task

The MBean Explorer supports several different types of connections. The tooling itself comes only with a default connection type, however other adopters can provide additional connection types that may require additional or non-spec behavior. Connections can be in either the connected state or the disconnected state. Some connection types (such as the default connection type) allow you to control the current state. Other connection types may not.

Similarly, some connection types may be able to be created, and others may not. The default connection type, for example, can be created and deleted at will. The AS Tools connection type, which represents a JBoss server, does not allow you this level of control. A JBoss JMX connection is created when a JBoss server is created in the server's view, and deleted when said server is deleted. The JMX connection for this server is in the connected state only when the server is started.

2.6.1. Establishing Connection

There are two ways to connect to an application with remote management enabled:

The	first	step	is	the	same	for	both	methods -	to
connect	to	а	MBean	Server	, click	the	New	Connection	icon



in the MBean Explorer menu bar.

The simple method is to specify the host, port (and optionally user name and password) and click the **OK** button.

On the **Advanced** tab you can set the server name (it will be displayed in **MBean Explorer**), and a URL to the remote server. For example, to connect to JBoss AS you need to set the **JMX URL** to

```
service:jmx:rmi://localhost/jndi/rmi://localhost:1090/jmxconnector
```

If it is required you can enter user name and password for the server connection.



Note

Only JMX URL based on RMI are supported.

References

3.1. MBean Explorer

The **MBean Explorer** displays the MBean features (both attributes and operations) in its hierarchy. Double-clicking on a feature will open an MBean Editor, displaying the page corresponding to the feature type and select the feature.



Figure 3.1. MBean Explorer Features

Since it is possible to have many MBean Editors opened at the same time, the MBean Explorer the Link With Editor button has 雪

to synchronize selections between the active **MBean Editor** and the **MBean Explorer** (and vice versa).

The **MBean Explorer** has also a filter that can be used to filter the available MBeans to show those that interest you.

For example, if you are only interested by MBeans related to memory, typing "memo" will show any node (domain, mbean, attribute, or operation) that matches that text, as well as that node's parents and children. So if an MBean matches, all attributes and operations from that bean will be displayed. If, however, an attribute or operation name (a leaf node) matches, only that node and its parents in the tree will be displayed.



Figure 3.2. Query Filter

The	Collapse	All	button
	_		

on the MBean Explorer toolbar is used to collapse all the MBeans and display only the domains. It is also possible to double click on a node to expand or collapse it.

3.2. MBean Editor

II Attributes		Attribute Details	
Name BaseDir	Value ./deploy/management	Name BaseDir Type java.lang.String	
StateString	Started	Description MBean Attribute. Permission 🍄	
State	3		
Name	DeploymentFileRepository	./deploy/management	late
< 111	>		

Figure 3.3. MBean Editor Pages

The MBean Editor is composed of several pages:

- the Attributes page
- the Operations page
- the Notifications page
- the Info page

The **Attributes** and **Operations** pages display a list for either the MBean attributes or operations, as well as details about the selection.

It is possible to toggle the layout between the list and the details either vertically (by default) horizontally icons or with the help of the special



in the right top corner of the editor.

o [©] jboss.admin:service=D	DeploymentFileRepository 🕴	- 0
jboss.admin:servio	ce=DeploymentFileRepository	
All Attributes		
Name	Value	
BaseDir	./deploy/management	
StateString	Started	
State	3	
Name	DeploymentFileRepository	
Attribute Details		
Name BaseDir		
Type java.lang		
Description MBean All Permission 🌮	ttribute.	
./deploy/management	t Dpda	ate
Attributes Operations N	otifications Info	

Figure 3.4. MBean Editor Horizontal Layout

♂ jboss.admin:service=[DeploymentFileRepository 🕴	- 8
jboss.admin:servi	ce=DeploymentFileRepository	=
All Attributes		
Name	Value	
BaseDir	./deploy/management	
StateString	Started	
State	3	
Name	DeploymentFileRepository	
Attribute DetailsNameBaseDirTypejava.langDescriptionMBean APermission%		
./deploy/managemen	update	
Attributes Operations N	lotifications Info	

Figure 3.5. Visual Page Editor

3.2.1. Notifications Page

The **Notifications** page provides the ability to subscribe or unsubscribe to an MBean to receive its notifications by checking or unchecking the **Subscribe** button in the right top corner.

The list of notifications is refreshed every time a new notification is received:

		=DeploymentFile			- 6	Subscrib
Timestamp	Туре	Message	User Data	Sequence Nur	Source	

Figure 3.6. MBean Editor Notifications Page



Note

It is only possible to subscribe to an MBean that emits notifications (i.e. they must be a NotificationBroadcaster).

Summary

This document has provided an overview of the functionality included with JXM Tools, as well as walking you through the steps on managing Tomcat, Eclipse Equinox or JBoss Instances and how to create new JMX connections. If you have questions or suggestions concerned both the documentation and tools behavior, you are welcome to JBoss Tools Users forum. Please, use Jira to report bugs and requests on documentation.

4.1. Other relevant resources on the topic

You can find the JBoss Developer Studio/JBoss Tools release documentation at *http://docs.jboss.org/tools* in the corresponding release directory.

The latest documentation builds are available at *http://download.jboss.org/jbosstools/nightly-docs*.

The JBoss JXM Wiki can be found at http://www.jboss.org/community/wiki/JBossMX

For more information about JMX technology please visit *JMX Technology Home Page* [http:// java.sun.com/javase/technologies/core/mntr-mgmt/javamanagement/]