# JBoss ESB Tools User Guide

Version: 3.2.1.GA



1. Introduction	1
1.1. What is ESB and JBoss ESB Tools?	1
1.2. Key Features of ESB Tools	1
2. Tasks	3
2.1. Creating a ESB Project	3
2.2. Using ESB Project Examples	13
2.3. Deploying a ESB Project	20
2.4. Creating a ESB File	26
2.5. Creating a ESB Action	29
2.6. Configuring ESB Runtime in Preferences	32
2.7. Using and Configuring SOA Platform	39
3. Reference	49
3.1. JBoss ESB Editor	49
3.1.1. Source View	49
3.1.2. Tree View	52
3.2. ESB Editor Features	75
3.2.1. ESB Syntax Validation	75
3.2.2. Support for XML Schema	75
3.2.3. Content Assist for ESB XML File	75
3.2.4. OpenOn for ESB XML File	76
3.2.5. Synchronized Source and Visual Editing	78
4. Summary	31
4.1. Other Relevant Resources on the Topic	31

## Introduction

#### 1.1. What is ESB and JBoss ESB Tools?

ESB (Enterprise Service Bus) is an abstraction layer on top of the implementation of an enterprise messaging system that provides the features that Service Oriented Architectures may be implemented with.

If you want to develop applications using ESB technology JBoss ESB also meets your needs. Read more about JBoss ESB at <a href="http://www.jboss.org/jbossesb">http://www.jboss.org/jbossesb</a>.

JBoss ESB Tools provides an ESB editor and wizard for creating an ESB file.

This guide will provide you with the information you need to install, configure and deploy JBoss ESB Tools. Information will also be provided on the use of the ESB Editor, which allows you to quickly develop an ESB file with fewer errors.

### 1.2. Key Features of ESB Tools

The table below lists the main features of the ESB plugin:

Table 1.1. Key Functionality of ESB Tools

Feature	Benefit	Chapter
JBoss Tools Project Examples Wizard	Quickly create example projects with a predefined structure.	Section 2.2, "Using ESB Project Examples"
JBoss Enterprise SOA Platform	The SOA Platform integrates specific versions of JBoss ESB, jBPM, Drools and the JBoss Enterprise Application Platform that are certified to work together in a single supported enterprise distribution.	Section 2.7, "Using and Configuring SOA Platform"
ESB Editor	JBoss ESB tooling includes a powerful editor with features including syntax validation, support for XML Schema and more.	

# **Tasks**

In this section we will focus on all concepts that JBoss Tools integrate for working with JBoss ESB.

### 2.1. Creating a ESB Project

In this chapter we suggest a step-by-step walk-through of creating a new ESB project. Let's try to create a new JBoss ESB project.

We will show you how to use the ESB Project Creation wizard for creating a new ESB project and setting basic ESB classpath.

Select  $File \rightarrow New \rightarrow Project...$  in the main menu bar or context menu for selected project and then  $ESB \rightarrow ESB$  Project in the dialog opened:





Figure 2.1. Select a Wizard dialog

Clicking *Next* brings you to the JBoss ESB Project wizard page where a project name, ESB version and target JBoss Runtime are to be specified. Specify, for example, *helloworld* as a Project name and accept the default ESB version.

<b>9</b>	New ESB Project Wizard	
JBoss ESB Project		
Create a new JBoss E	SB project.	
Project name: hellow	world	
Project location		
✓ Use default locati	ion	
Location: /home/ma	atthew/redhat/workspaces/workspace-jbds4/	helld
Target runtime		
jboss-eap Runtime		⇒ Nev
JBoss ESB version		
4.9		
Configuration		
Default Configuration	on for jboss-eap Runtime	
J 3 .	t for working with jboss-eap Runtime runtime I to add new functionality to the project.	. Additior
?	< Back Next > Cancel	

Figure 2.2. JBoss ESB Project wizard

By clicking the **Modify** button you can open *Project Facets Wizard* page, where you can select facets that should be enabled for this project. On the *Project Facets Wizard* page you can also configure runtime for the application



Click the **Next** button to move to the next step in the wizard, where you can select the source and output folders.




Figure 2.4. Project Facets Wizard

Next step provides you an opportunity to configure your project for building a java application

Clicking the **Next** button on this form brings you to the ESB facet installation page where you can specify the ESB Content Directory. ESB Content Directory is a folder that contains the most of artifacts that an ESB archive needs. You also can configure ESB libraries to the project by selecting a ESB runtime using one of the options:

#### 1. Use Server Supplied ESB Runtime

- 2. Select a ESB runtime from the JBoss ESB runtime list predefined in the preferences. If you choose the first option, make sure that the project has the Target JBoss Runtime set and this runtime has a ESB runtime installed.
- 3. Choose ESB Config Version. From the version 3.1.0 JBoss ESB Tools supports three different jboss-esb.xsd versions: jbossesb-1.0.1.xsd, jbossesb-1.1.0.xsd and jbossesb-1.2.0.xsd.



#### Note:

If you use ESB 4.7 you should select jbossesb-1.2.0.xsd.





Figure 2.5. Install ESB facet step

Click the Finish button and a ESB project with the default jboss-esb.xml file will be created.



## 2.2. Using ESB Project Examples

JBoss Tools provides a Project Example wizard that is an easy way for users to create some kinds of projects to be used as examples with some predefined structure. Let's start creating a ESB project using this wizard.

Before creating a ESB project example create JBoss Runtime with name *JBoss 4.2 Runtime*, it will be used by your ESB project example.

Select  $File \rightarrow New \rightarrow Other...$  in the main menu bar or context menu for selected project and then JBoss Tools  $\rightarrow$  Project Examples in the New dialog:




Figure 2.7. Select a wizard - Project Examples

Clicking the **Next** button brings you to the wizard page where you can select a ESB project example from the example list.

<b>®</b>	New Project Example
Project Example	
Import Project Example	
☐ Show experimental sites	
Site: All	
Projects:	
type filter text	
▶ Seam	
▶ Portlet	
ESB for SOA-P 4.3	
ESB for SOA-P 5.0	
Designer	
Description:	
Project name:	
Project size:	
URL:	

Figure 2.8. Project Example Wizard

✓ Show the Quick Fix dialog



#### Note:

Under the Projects section you can find two categories related to ESB:

- ESB for SOA-P 4.3
- ESB for SOA-P 5.0

It means that if you use a runtime pointed to a SOA-P 5.0, you should download the examples from the *ESB for SOA-P 5.0* category in order to avoid the incompatibility errors.

Every ESB example has two projects, one is a ESB project and another is a Java project used to test the ESB project.

Here is a list of ready examples available in both categories (ESB for SOA-P 4.3 and ESB for SOA-P 5.0):

- JBoss ESB HelloWorld Example demonstrates the minimal files necessary to make a basic ESB component execute as well as to prove that the ESB is properly configured.
- JBoss ESB HelloWorld Action Example demonstrates the use of multiple action invocations
  from a single configuration. You can use a single Action class and make multiple method calls
  or use multiple Action classes.
- JBoss ESB HelloWorld Email Example demonstrates how to configure a mail gateway using
  a JCA mail adapter and a Camel mail endpoint. Both gateways route the messages through a
  JMS queue and finally to your action class for processing.
- JBoss ESB HelloWorld File Action Example demonstrates using the File gateway feature
  of the JBoss ESB. Files that are found in a particular directory with a particular extension are
  sent to a JMS queue with actions for processing.
- JBoss ESB Web Service consumer1 Example demonstrates how to consume a 181 Web Service in an ESB action.
- JBoss ESB Web Service producer Example demonstrates how to deploy a JSR181 Webservice endpoint on JBossESB using the SOAPProcessor action.
- JBoss ESB Smooks CSV -> XML Example demonstrates how to transform a comma separated value (CSV) file to an XML.
- JBoss ESB Smooks XML -> POJO Example demonstrates the use of Smooks performing a simple transformation by converting an XML file into Java POJOs.
- JBoss ESB Smooks XML -> XML date-manipulation Example demonstrates how to manually define and apply a Message Transformation within JBoss ESB.

• JBoss ESB Smooks XML -> XML Example - a very basic example of how to manually define and apply a Message Transformation within JBoss ESB. It applies a very simple XSLT to a SampleOrder.xml message and prints the before and after XML to the console.

We will take as our example JBoss ESB HelloWorld Example ESB project:

•	New Project Example
roject Exam	ole
mport Project	Example
Show experi	mental sites
Site: All	
Projects:	
type filter text	
▶ Seam	
▶ Portlet	
ESB for SOA	A-P 4.3
♥ ESB for SOA	A-P 5.0
JBoss ES	B HelloWorld Example - ESB
JBoss ES	B HelloWorld Action Example - ESB
Description:	
jboss-soa-p.5.0 This exam	mport this example, please make sure that there is a runtim O Runtime" in the workspace. ple is to prove that the ESB is is properly configured and hap emonstrate the needed minimal files to make a basic ESB co
Project name:	helloworld
Project size:	1.05M
URL:	http://anonsvn.jboss.org/repos/jbosstools/workspace/Denn
	ols ESB Project Examples inple has some requirements that could not be cally configured. When importing the example you might

see some errors which would need fixing manually or via Quick

✓ Show the Quick Fix dialog.

Select the **JBoss ESB HelloWorld Example** ESB project and then click the **Finish** button. As a result you will get two projects created:




Figure 2.10. JBoss ESB Project Examples: helloworld and helloworld\_testclient

Deploy the HelloWorld ESB project and run a test class in the client Java project to see the test result in the Console view.

## 2.3. Deploying a ESB Project

In this chapter you will see how to deploy a ESB project using the WTP deployment framework.

Before deploying the project, open the Servers View by selecting  $Window \rightarrow Show \ View \rightarrow Other$   $\rightarrow Server \rightarrow Servers$ , create a JBoss Server in the Server view and start it, and then right click the created JBoss server, select Add and  $Remove\ Projects$ , and add the ESB projects you want to deploy from the left side to the right side in the opened dialog.





Figure 2.11. Add and Remove Projects

Click the **Finish** button to add the project to the server. You also can drag the ESB project from the Project View to the server.




#### Figure 2.12. Servers View

Thus, you have just added the ESB project to the JBoss server module list. Right click the JBoss Server and select **Publish** to publish the project on the server. You can check the deploying result in the Console view.

The **Run** and **Debug** options work on ESB projects causing a (re)deploy for a user designated server.

You can also use the "Finger touch" for a quick restart of the project without restarting the server:



#### Figure 2.13. Finger Touch button

The "Finger" touches descriptors dependent on project (i.e. web.xml for WAR, application.xml for EAR) and now it is also available for jboss-esb.xml in ESB projects.

You can also deploy your ESB project as an .esb archive. Right-click on the project, choose **Export**:

Ne <u>w</u> Go <u>I</u> nto		>
Open in <u>N</u> ew Window Ope <u>n</u> Type Hierarchy		F4
Sho <u>w</u> In	Shift+Alt+W	_
<u>C</u> opy Cop <u>y</u> Qualified Name	Ctrl+	-C
<u>P</u> aste	Ctrl-	٠V
<u>D</u> elete	Dele	te
<u>B</u> uild Path		>
<u>S</u> ource	Shift+Alt+S	>
Refac <u>t</u> or	Shift+Alt+T	>
<u>I</u> mport		
Exp <u>o</u> rt		
Re <u>f</u> resh	ı	-5
Clo <u>s</u> e Project		
Close <u>U</u> nrelated Projects		
Assign Working Sets		
<u>R</u> un As		>
<u>D</u> ebug As		>
<u>P</u> rofile As		>
Mark as Deployable		
<u>V</u> alidate		
T <u>e</u> am		>
Comp <u>a</u> re With		>
Restore from Local History		
gure 2.14. Export of ESB project Spring Tools		<b>&gt;</b>
TestNG		>
Configure		>

Choose  $ESB \rightarrow ESB$  File and click Next:




Figure 2.15. Choosing ESB File

And finally export the ESB project to the file system: choose the destination, choose the target runtime if need a specific one and make the appropriate settings for the archive. Then click **Finish**.




Figure 2.16. ESB Export

Your project is deployed as an .esb archive.

An ESB archive can be created for ESB projects only. It is also possible to deploy an .esb archive to a JBoss AS based server with JBoss ESB installed.

## 2.4. Creating a ESB File

In this chapter we suggest a step-by-step walk-through of creating your own simple file. Let's try to organize a new ESB file.

We will show you how to use the Creation wizard for creating a new ESB file.

At first you should open a project that has the ESB facet enabled. Select  $File \rightarrow New \rightarrow Other...$  in the main menu bar or context menu for selected project and then  $ESB \rightarrow ESB$  File in the New dialog:




Figure 2.17. Select a wizard - ESB File

Clicking *Next* brings you to the wizard page where a folder, a name and a version for the file should be specified. Choose, for example, *jboss-esb.xml* as the name and accept the selected projects folder and the default version.



#### Note:

From the version 3.1.0 JBoss ESB Tools supports three different jboss-esb.xsd versions: jbossesb-1.0.1.xsd, jbossesb-1.1.0.xsd and jbossesb-1.2.0.xsd. If you use ESB 4.7 you should select jbossesb-1.2.0.xsd.




Figure 2.18. Folder, Name and Version for ESB file

Thus, your file will be created in the selected projects folder by default. If you want to change the folder for your future file click *Browse...* button to set needed folder or simply type it.

Clicking on Finish results in the file being generated. The wizard creates one xml file.

## 2.5. Creating a ESB Action

From this chapter you will find out how to create a ESB Action Java File .

At first you need to open a ESB or simple Java project. Then you should select  $File \rightarrow New \rightarrow Other$  in the main menu or from the context project menu. Then click  $ESB \rightarrow ESB$  Action in the New dialog.




Figure 2.19. Select a wizard - ESB Action

After that click *Next* and you will be brought to the *New ESB Action* wizard. In this wizard the class name should be specified, also you can set a package or add a interface as for any Java class.

<b>9</b>	New ESB Action
ESB Action	
Create a new Java	class.
	<ul> <li>As AbstractActionPipelineProcessor implementation</li> </ul>
Source folder:	helloworld/src
Package:	actions
☐ Enclosing type:	
Name:	Action
Modifiers:	● public ○ default ○ private ○ protected
	□ abstract □ final □ static
Superclass:	org.jboss.soa.esb.actions.AbstractActionPipelineProces
Interfaces:	
Do you want to add	comments? (Configure templates and default value here
	☐ Generate comments
2	< Back Next > Cano
•	< Back Next > Cano
Figure 2.20. New ESB Ac	tion wizard

31

As a result, the ESB Action Java File will be created in the selected package and it will have org.jboss.soa.esb.actions.AbstractActionPipelineProcessor as superclass.


Clicking on *Finish* will generate the ESB Action class. Also this class will become available in ESB Editor wizards.

### 2.6. Configuring ESB Runtime in Preferences

In this chapter you will learn how to predefine a JBoss ESB runtime on the Preferences page.

You may already know, there are two ways to set JBoss ESB runtime when creating a ESB project, one is to use the project target JBoss runtime, and another is to select a JBoss ESB runtime predefined in JBoss Tools preferences. Let's configure it.

Select Window  $\rightarrow$  Preferences  $\rightarrow$  JBoss Tools  $\rightarrow$  JBoss ESB Runtimes to open the JBoss ESB Runtime Preferences page where you can add, remove and Edit a JBoss ESB runtime.



Select *Add* to open a dialog where you can specify the JBoss ESB runtime location, name and version number. It's also possible to define configuration if you point the home location to a Jboss AS or SOA-p, in case you select a standalone ESB runtime location, the configuration combo will be empty and should be ignored. You can also customize the libraries of the runtime by checking the *Customize JBoss ESB Runtime jars* checkbox.




Figure 2.22. Configure new JBoss ESB Runtime

The new JBoss ESB Runtime will be configured. Click **Finish** to finish and save the preferences. You can use the configuration when creating a JBoss ESB project.

When a ESB runtime is configured for your ESB project you are able to change it to any other using the classpath container page for ESB runtime. To do that, turn to the Package Explorer view and right-click the "JBoss ESB Runtime" library. Select *Properties* and a table listing all available JBoss ESB runtimes will appear:




Figure 2.23. Classpath Container Page to change ESB runtime

Choose one of them to set to the ESB project and click Ok.

ESB container allows Source and JavaDoc locations to be set via the Properties dialog on each contained .jar: right-click on any .jar file, select *Properties*. Choose *Java Source Attachment* and select location (folder, JAR or zip) containing new source for the chosen .jar using one of the suggested options (workspace, external folder or file) or enter the path manually:




Figure 2.24. Classpath Container: Java Source Attachment

Click on Apply and then on Ok.

To change Javadoc Location choose *Javadoc Location* and specify URL to the documentation generated by Javadoc. The Javadoc location will contain a file called *package-list*:




Figure 2.25. Classpath Container: Javadoc Location

Click on Apply and then on Ok.

## 2.7. Using and Configuring SOA Platform

In this chapter you will learn what the JBoss Enterprise SOA Platform is and how you can configure it to use for your ESB projects.


JBoss Enterprise SOA Platform delivers a flexible, standards-based platform to integrate applications, SOA services, business events and automate business processes. The SOA Platform integrates specific versions of JBoss ESB, jBPM, Drools and the JBoss Enterprise Application Platform that are certified to work together in a single supported enterprise distribution.

Having configured JBoss Enterprise SOA Platform for your ESB project you don't need to install and configure ESB server and runtime as they are already included.

Check here to find more details on the platform: *JBoss Enterprise SOA Platform* [http://www.jboss.com/products/platforms/soa] and *JBoss Enterprise SOA Platform Component Details* [http://www.jboss.com/products/platforms/soa/components].

You can find out what is SOA here: *Basics of SOA* [http://www.jboss.org/jbossesb/resources/SOABasics.html] and *SOA and EOA* [http://www.jboss.org/jbossesb/resources/SOAEOA.html].

To configure the JBoss Enterprise SOA platform select  $Window \rightarrow Preferences \rightarrow Server \rightarrow Runtime Environments$ , which will open the Server Runtime Environments Preferences page where you can add, remove and edit a Server Runtime Environment.



Select *Add*, choose *JBoss 5.0 Runtime* as a type of runtime environment, check the *Create a new local server* checkbox and click *Next*:





Figure 2.27. Type of Server Runtime Environment

On the next step you can specify a name of the server runtime environment and browse to its location. Click *Finish* to add the server runtime environment.



Now you have your SOA platform configured. To check the configuration create a ESB Project using instructions described *Section 2.2*, "Using ESB Project Examples". As a result you will have two projects created:




Figure 2.29. Helloworld Projects Created

Then you will need to add JBoss ESB libraries to your projects to configure the SOA server runtime exactly for your projects. Right-click on your project, select **Build Path** → **Add Libraries**:

New	>	
Go Into		
Open in New Window		
Open Type Hierarchy	F4	
Show In	Shift+Alt+W >	
Сору	Ctrl+C	
Copy Qualified Name		
Paste	Ctrl+V	
Delete	Delete	
Build Path	<del></del>	Link <u>S</u> ource
Source	Shift+Alt+S >	<u>N</u> ew Source Folder
Refactor	Shift+Alt+T >	<u>U</u> se as Source Folder
Import		Add External Archi <u>v</u> es
Export		Add <u>L</u> ibraries
Refresh	F5	Configure Build Path
Close Project		
Close Unrelated Projects		
Assign Working Sets		
Run As	>	
Debug As	>	
Profile As	>	
Mark as Deployable		
Validate		
Team	>	
Compare With	>	
Restore from Local History		
Figure 2.30. Add Libraries	>	
Spring Tools	>	
TestNG	>	
Configure	>	

Choose JBoss ESB Libraries and click Next:




Figure 2.31. ESB Libraries

Select the necessary runtime to add to the project classpath:




Figure 2.32. Select a ESB runtime

Click Finish.

Now you can deploy your Helloworld project to the server and run a test class in the client Java project to see the test result in the Console view.

# Reference

This chapter includes detailed reference information about JBoss ESB Tools.

### 3.1. JBoss ESB Editor

ESB editor has lots of useful features, they are described in details in this chapter.

ESB File Editor is a powerful and customizable tool which allows developing an application using ESB technology.

ESB file editor has two tabs: Tree and Source.

#### 3.1.1. Source View

You can easily switch from Tree to Source by selecting the Source tab at the bottom of the editor and work in Source view.

```
<?xml version="1.0"?>

⊖<ibossesb
</p>
    xmlns="http://anonsvn.labs.jboss.com/labs/jbossesb/trunk/pi
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:s
    oviders>
     <jms-provider connection-factory="ConnectionFactory" name=</pre>
      <jms-bus busid="qucikstartGwChannel"/>
      <jms-bus busid="quickstartEsbChannel"/>
     </jms-provider>
    </providers>
    <services>
     <service category="MyCategory" description="A Test ESB Ser</pre>
      steners>
       tener name="JMS-Gateway"/>
       tener name="helloworld"/>
      </listeners>
      <actions>
       <action class="org.jboss.soa.esb.actions.converters.0bje</pre>
        property name="class-processor"/>
        property name="class-method"/>
       </action>
       <action class="org.jboss.soa.esb.actions.converters.0bje</pre>
        property name="class-processor"/>
        property name="class-method"/>
       </action>
       <action class="org.jboss.soa.esb.actions.converters.0bje</pre>
        property name="class-processor"/>
        property name="class-method"/>
       </action>
      </actions>
     </service>
    </services>
   </jbossesb>
```

Figure 3.1. Source View

<

Ш

The Source view for the editor displays a text content of the ESB file. It is always synchronized with Tree view, so any changes made in one of the views will immediately appear in the other.

No matter what view you select, you get full integration with Outline view. For example, you can work in the Source view with the help of the Outline view. The Outline view shows a tree structure of the ESB file. Simply select any element in the Outline view and it will jump to the same place in the Source editor, so you can navigate through the source code with Outline view.

```
💷 *jboss-esb.xml 🟻
   <?xml version="1.0"?>
  ⊖<jbossesb</pre>
    xmlns="http://anonsvn.labs.jboss.com/labs/jbossesb/trunk/product/etc/schemas/xml/jboss
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://anons
   oviders>
     <jms-provider connection-factory="ConnectionFactory" name="JBoxxMQ">
      <jms-bus busid="qucikstartGwChannel"/>
      <jms-bus busid="quickstartEsbChannel"/>
     </jms-provider>
    </providers>
    <services>
     <service category="MyCategory" description="A Test ESB Service" name="SimpleListener"</pre>
      steners>
       tener name="JMS-Gateway"/>
       tener name="helloworld"/>
      </listeners>
      <actions>
       <action class="org.jboss.soa.esb.actions.converters.ObjectInvoke" name="action1">
        property name="class-processor"/>
        property name="class-method"/>
       </action>
       <action class="org.jboss.soa.esb.actions.converters.ObjectInvoke" name="action2">
        property name="class-processor"/>
        property name="class-method"/>
       </action>
       <action class="org.jboss.soa.esb.actions.converters.ObjectInvoke" name="testStore">
        property name="class-processor"/>
        property name="class-method"/>
       </action>
      </actions>
     </service>
    </services>
   </jbossesb>
Tree Source
```


Figure 3.2. Outline View

#### 3.1.2. Tree View

You can switch to Tree. The Tree view for the editor displays all ESB artifacts in a tree format. By selecting any node you can see and edit its properties which will appear in the right-hand area. For example, a Provider:

*jboss-esb.xml ⊠ Boss ESB 1.3 Editor		
oss ESB 1.3 Editor		
,055 205 215 241101		
jboss-esb	<b>→</b> JMS Provider	
	Name:	JBoxxMQ
⇒ WAR Security	Connection Factory:	ConnectionF
▽ 🗁 Providers	▼ Properties	
<ul> <li>✓</li></ul>	Name	Value
<ul> <li>✓ ➢ Services</li> <li>✓ ễ SimpleListener</li> <li>☑ Security</li> <li>✓ ➢ Listeners</li> <li>⑥ JMS-Gateway</li> </ul>		
nelloworld	→ Channel list	
Actions  Action1	ID qucikstartGwChanr	nel
action1 action2 testStore	quickstartEsbChan	
	<b>→</b> Advanced	
	JNDI Context Factory	y:
	JNDI pkg Prefix:	
	JNDI URL:	
re 3.3. Tree View		


Some properties are represented as links to the associated editors.



▼ Action		
Name:	action1	
Class:	org.jboss.soa.e	
Process:	displayMessage	
▼ Properties		
Name		

class-processor


class-method



Alerti engthThreshold:

AlertLengthThreshold:

Now when editing ESB actions which refer to other files (Drools, Groovy, Smooks, etc.), the label for the field turns into a link to launch the editor associated with that type of file.



## JBoss ESB 1.3 Editor

## 

- - - WAR Security
  - - - op quickstartEsbChannel
  - - 🗢 🧠 SimpleListener
      - Security
      - - helloworld
      - - - action2
          - testStore
          - 🐞 simple-transform

#### Smooks Action

Name:

simple-tr

Class:

org.jboss

Smooks Config:

/smooks

Process:

#### Advanced

Get Payload Location:

Set Payload Location:

Mapped Context Objects:

Result Type:

Java Result Bean Id:

Report Path:

Message Profile:

Figure 3.5. Property Link to the Associated Editor

Adding, editing or deleting of some artifacts operations are available right in the Tree view. Right-click any node and select one of the available actions in the context menu. For example, you can easily add a new Provider:





Figure 3.6. Adding New Provider

#### Chapter 3. Reference

Then you can add Channels and Properties for the Providers the same way or using the forms with Add, Edit and Remove buttons to the right.

You can easily add a new Service too:



The same way you can create a listener for service and other elements of ESB:

### iboss-esb.xml iboss-esb JBoss ESB 1.3 Editor ▼ jboss-esb Listeners Name JMS-Gateway Globals WAR Security helloworld qucikstartGwChannel 🗢 🦏 SimpleListener Security 🔻 🗁 Lister New 🛍 JM Camel Gateway... Paste Ctrl + V ne he FS Listener... Delete Delete FTP Listener... 🕨 🗞 ac **Properties** Groovy Listener... action2 Hibernate Listener... testStore HTTP Gateway... 🎨 simple-transform JBR Listener... JCA Gateway... JMS Listener... Scheduled Listener... SQL Listener... UDP Listener...

Figure 3.8. Adding New Listener for Service

#### Chapter 3. Reference


The same actions can be done in the right part of Tree view tab (Form editor) using Add, Edit and Remove buttons.

Filter can be also edited this way

## ■ \*jboss-esb.xml □ JBoss ESB 1.3 Editor ▼ jboss-esb ▼ FS Message Filter Directory: Input Suffix: WAR Security Advanced Work Suffix: op qucikstartGwChannel Post Delete: Post Rename: 🗢 🦏 SimpleListener Security Post Directory: Post Suffix: MS-Gateway helloworld Error Delete: Error Directory: ϔ Filter Error Suffix: & action1 action2 testStore 🎨 simple-transform Figure 3.9. Editing Filter

III

In order to add a new custom Action to your ESB XML file you should select the Actions node under the Services, then right-click and choose  $\textbf{New} \rightarrow \textbf{Custom Action}$ .



Or instead make use of Add... button in the Form editor on the left.

# অ \*jboss-esb.xml ¤

### JBoss ESB 1.3 Editor

#### ▼ jboss-esb

- - - WAR Security
  - → Providers
    - - ▶ •⇒ qucikstartGwChannel
      - ▶ •⇒ quickstartEsbChannel
  - - 🗢 🧠 SimpleListener
      - Security
      - - MS-Gateway
        - helloworld
        - - 푸 Filter

#### 🔻 🍖 Actions

- - action2
  - testStore
  - imple-transform

Figure 3.11. Adding New Custom Action in the Form Editor

Actions L

MEP:

Request Loc

Response Lo

Actions

Name

action1

action2

testStore

simple-tra

Advance

In XSD:


Out XSD:

Fault XSD:

Webservice

Validate:

Addressing:



Then you will see Add Action wizard. There is a need to specify Action name and Action Java class.




Figure 3.12. Add Action Wizard

To get a help with finding a proper class you can select *Browse* to open Select class dialog.




Figure 3.13. Select class dialog

Moreover it's possible to type a Process name or select it with Edit Process dialog which is called out by clicking *Browse*.




Figure 3.14. Edit Process dialog

As you can see on the both figures above, the context menu will also prompt you to insert one of the Actions that are supplied out-of-the-box with JBoss ESB. After choosing one an appeared New Pre-Packed Action wizard will ask you to fill out a name field and other fields specific for each Action property. For example, for *Content Based Router* Action the wizard looks as follows:

<b>®</b>	Add Content Based Router
ESB Content Based Router	
Attribute Name must be set.	
Name:*	
CBR Alias:*	
Process:	
Rule Set:	
Rule Language:	
Rule Reload:	Default(false)
?	Cancel

Figure 3.15. Add Pre-Packed Action Wizard

After confirming creating the Action you can see it in the Tree under the *Actions* node and preview as well as edit its settings in the Form editor on the left.

# iboss-esb.xml iboss-esb JBoss ESB 1.3 Editor ▼ jboss-esb

WAR Security

odposition
odposition
parallel
paralle

🗢 🦏 SimpleListener

Security

MS-Gateway

helloworld

Filter

action1

action2

testStore

simple-transform

scope

express

Figure 3.16. Form Editor for Content Based Router

#### 

Name:

Conter

Class:

org.jbc

CBR Alias:

org.jb

Rule Set:

MyESB

Rule Language:

XPathL

Rule Reload:

true

Process:

split

#### Route List

Destination Nar Service

#### ▼ Namespace List

Prefix

express

ESB editor can recognize some specific objects. On the figure you can see org.jboss.soa.esb.actions.ContentBasedRouter in the Class section.

#### 3.2. ESB Editor Features

JBoss ESB tooling has powerful editor features that help you easily make use of content and code assist.

This last chapter covers capabilities on how you can use ESB editor.

#### 3.2.1. ESB Syntax Validation

When working in JBoss ESB editor you are constantly provided with feedback and contextual error checking as you type. In the Source viewer, if at any point a tag is incorrect or incomplete, an error will be indicated next to the line and also in the Problems view below.

#### 3.2.2. Support for XML Schema

JBoss ESB Framework fully supports XML files based on schemas as well as DTDs (see Figure 3.1, "Source View").

The schema checks the child elements of any kind of provider element; the ESB generates errors on startup if you attempt to define an incorrect combination (e.g.: a jms-bus inside an ftp-provider).



#### Note:

The schema used behind ESB editor now uses the latest version available (from SOA-P 4.3). This removes the errors/warnings some users have reported seeing when using SOA-P specific esb.xml files.

#### 3.2.3. Content Assist for ESB XML File

When you work with any ESB XML file Content Assist is available to help you. It provides popup tip to help you complete your code statements. It allows you to write your code faster and with more accuracy. Content assist is always available in the Source mode. Simply type *Ctrl-Space* to see what is available.

Content Assist for ESB XML file:



Figure 3.17. Content Assist for ESB XML file

Content Assist for attributes:




Figure 3.18. Content Assist for attributes

#### 3.2.4. OpenOn for ESB XML File

ESB file comes with the OpenOn feature that allows to make use of multiple file references in the file just with a click and the *Ctrl* key hold down.

The OpenOn is implemented for different types of files/pages inside the <action> tag: .xsd, .xml, etc.

```
- 0
dest-name="queue/quickstart_helloworld_Request_gw" dest-type="QUEUE"/>
     </jms-bus>
     <jms-bus busid="quickstartEsbChannel">
      <jms-message-filter</pre>
       dest-name="queue/quickstart_helloworld_Request_esb" dest-type="QUEUE"/>
     </jms-bus>
    </jms-provider>
   </providers>
   <services>
    <service category="FirstServiceESB" description="Hello World" name="SimpleListener"</pre>
     steners>
      <jms-listener busidref="quickstartGwChannel" is-gateway="true" name="JMS-Gateway"</pre>
      <jms-listener busidref="quickstartEsbChannel" name="helloWorld"/>
     </listeners>
     <actions mep="OneWay">
      <action
       class="org.jboss.soa.esb.samples.quickstart.helloworld.MyJMSListenerAction"
      name="action1" process="displayMessage"/>
      <action class="org.jboss.soa.esb.actions.SystemPrintln" name="action2">
       property name="message"/>
       property name="printfull" value="true"/>
      </action>
      <!-- The next action is for Continuous Integration testing -->
      <action class="org.jboss.soa.esb.actions.TestMessageStore" name="testStore"/>
      <action class="org.jboss.soa.esb.smooks.SmooksAction" name="smooks">
       property name="smooksConfig" value="META-INF/smooks-config.xml"/>
      </action>
     </actions>
    </service>
Tree Source
```

Figure 3.19. OpenOn for smooks configuration file

It is also available for classes:

```
- -
🔯 jboss-esb.xml 🔀
     <jms-bus busid="quickstartEsbChannel">
      <jms-message-filter
      dest-name="queue/quickstart_helloworld_Request_esb" dest-type="QUEUE"/>
     </jms-bus>
    </jms-provider>
   </providers>
   <services>
    <service category="FirstServiceESB" description="Hello World" name="SimpleListener"</pre>
     <jms-listener busidref="quickstartOwChannel" is-gateway="true" name="JMS-Gateway"</pre>
     <jms-listener busidref="quickstartEsbChannel" name="helloWorld"/>
     </listeners>
     <actions mep="OneWay">
      <action
      class="org.jboss.soa.esb.samples.quickstart.helloworld.MyJMSListenerAction"
      name="action1" process="displayMessage"/>
      <action class="org.jboss.soa.esb.actions.SystemPrintln" name="action2">
      property name="message"/>
      property name="printfull" value="true"/>
      </action>
      <!-- The next action is for Continuous Integration testing -->
      <action class="org.jboss.soa.esb.actions.TestMessageStore" name="testStore"/>
      <action class="org.jboss.soa.esb.smooks.SmooksAction" name="smooks">
      </action>
     </actions>
    </service>
   </services>
  </ibossesb>
                                                                                  >
Tree Source
```

Figure 3.20. OpenOn for classes

#### 3.2.5. Synchronized Source and Visual Editing

ESB file can be edited in either source or extra visual modes at the same time.

JBoss Tools provide you two different editors to speed your development: a graphical view (Tree) and source (Source). At the same time, you always have full control over esb source file. Any changes you make in the source view will immediately appear in the tree view. Both views are synchronized, you can edit the file in any view.




Figure 3.21. Two Views are Synchronized

## Summary

On the whole, this reference supplies you with all necessary information on the functionality that JBoss ESB plugin provides for work with JBoss ESB.

We hope, this guide helped you to get started with the JBoss ESB Tools. For additional information you are welcome on *JBoss forum* [http://www.jboss.com/index.html? module=bb&op=viewforum&f=201].

#### 4.1. Other Relevant Resources on the Topic

You can find a set of benefits and other extra information on:

- JBoss ESB [http://www.jboss.org/jbossesb]
- JBoss Wiki [http://community.jboss.org/en/wiki]
- JBoss ESB Documentation Library [http://www.jboss.org/jbossesb/docs/index.html]

The latest JBoss Tools/JBoss Developer Studio documentation builds are available on the *JBoss Tools nightly documentation page* [http://download.jboss.org/jbosstools/nightly-docs/].